

KEY FEATURES

- > Low voltage piezo ceramic
- > Optimal preload for high dynamics
- > Mechanical Amplification
- > Compact Size
- > High Resolution

RELATED PRODUCTS

- > CTEC benchtop controllers
- > CTEC OEM controllers

AVAILABLE OPTIONS

- > Vacuum compatibility
- > Ultra High Vacuum



NON CONTRACTUAL PICTURE

PARAMETER	VALUE	UNIT
> Quasistatic performances		
Nominal Stroke	130	µm
Min stroke	120	µm
Resolution ⁽¹⁾	7.4	nm
Blocked force	3.2	N
Stiffness	0.024	N/µm
> Dynamic performances		
Resonance frequency (free-free) ⁽²⁾	3 800	Hz
Resonance frequency (blocked-free) ⁽³⁾	1 100	Hz
Force limit ⁽⁴⁾	2.2	N
> Control & driving		
Voltage range	-20 ... 150	V
Capacitance ⁽⁵⁾	0.18	µF
> Dimensions & interfaces		
Height	5	mm
Length	14	mm
Width incl wires	9	mm
Mass	1.3	g
> Standard mechanical interfaces	See ICD	
> Electrical interface	See ICD	

ANNOTATIONS

(1) Quasistatic excitation. With standard LA75 range amplifier. SNR=85dB computed as RMS output signal /RMS output Noise floor at [0;200Hz]

(2) Free-free: The actuator mounts are free

(3) Blocked-free: The actuator is fixed to a mechanical support assumed infinitely stiff

(4) Maximum pulling or pushing external force, valid up to 90% of the blocked-free resonance frequency of the actuator

(5) Capacitance +/- 20%, at 1 V RMS, low frequency, without load

